

RECOMMENDED OPERATING CONDITIONS

MODEL #	PART #	PRESSURE DIFFERENTIAL	STORAGE TEMPERATURE RANGE	pH RANGE	OPERATING PRESSURE RANGE	WATER TURBIDITY
MG-10MCB	255420-43	88 psi (6.1 bar) max	35-104° F (2.0-40° C)	2-12	5-88 psi (0.35-6.1 bar) max	<1 NTU

SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (ABSOLUTE)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*	ESTIMATED CAPACITIES**
MG-10MCB	255420-43	2.88" x 10.28" (73 mm x 261 mm)	0.15	11 psi @ 1 gpm (0.76 bar @ 3.8 Lpm)	200-600 gallons (757-2,271 L)

*Based on manufacturer's internal testing.

**Capacities may vary depending on local water quality, type of pre-filtration and acceptable minimum flow rate.

Not certified for sale in California, Iowa, or Wisconsin

NOTE: Cartridge not intended for converting wastewater or raw sewage into drinking water

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Distributed by



80L-B0F • Fort Collins, CO 80524

970.204.4758 • Fax: 970.204.4764 Brandon@IndustrialFilterSource.com

www.IndustrialFilterSource.com



© 2015 Pentair Residential Filtration, LLC. All rights reserved.

†For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com.

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310053 Rev D MY15